## Partition Standards For Commercial Tenant Improvements

- I. Minimum partition components to be per steel and wood stud tables below with I/2" drywall on both sides. 5/8" type "X" drywall is required for I hour fire resistive construction.
- 2. Minimum bracing shall consist of 2-1/2" metal studs installed at 4' on center, 45 degrees or less from the horizontal from top track or plate to structure above. Bracing is required where the horizontal span (perpendicular to the plane of the wall) is 8' or greater from support to support. Maximum distance from top of partition to structure above is 6'.

Récomendations '
Full Height Mtl. Stud Full Height

Full Height Wood Stud

Concrete Slab

20'-0" Max.

Alt. Bracing Detail

## 6-#6 Ga. Screws Ea. Flange Ea. Side of Splice Top or Bottom Track Piece of Stud 24" Min. Long

Steel Track Splice



Wood Top Plate Splice

## TABLE "A"-Maximum Stud Height


EQ.

Mood Studs			Plate Nailing
2×4@16"	2-1/2" 25 <i>G</i> A	3-1/2" 25 <i>G</i> A	3'-0" o.c.
2x6@l6"	2-1/2" 25 GA	3-1/2" 25 <i>G</i> A	2'-6" o.c.
2x6@l6"	3-1/2" 20 GA	3-1/2" 20 GA	2'-3" o.c.
	3-1/2" 20 GA	6" 24 GA	2'-3" o.c.
	6" 24 GA	4" 20 GA	2'-0" o.c.
	4" 20 GA	5-1/2" 20 GA	1'-9" o.c.
	5-1/2" 20 GA	6" 20 GA	1'-6" o.c.
	5-1/2" 18 GA	6" 18 GA	1'-3" o.c.
	8" 18 GA	8" 18 GA	1'-0" o.c.
	Studs 2x4@16" 2x6@16" 2x6@16"	Studs       12" o.c.         2x4@16"       2-1/2" 25 GA         2x6@16"       2-1/2" 25 GA         2x6@16"       3-1/2" 20 GA         3-1/2" 20 GA         6" 24 GA         4" 20 GA         5-1/2" 20 GA         5-1/2" 18 GA	Studs       12" o.c.       16" oc.         2x4@16"       2-1/2" 25 GA       3-1/2" 25 GA         2x6@16"       2-1/2" 25 GA       3-1/2" 25 GA         2x6@16"       3-1/2" 20 GA       3-1/2" 20 GA         3-1/2" 20 GA       6" 24 GA         6" 24 GA       4" 20 GA         4" 20 GA       5-1/2" 20 GA         5-1/2" 20 GA       6" 20 GA         5-1/2" 18 GA       6" 18 GA

Western Metal Studs ICC No. 2274 Angeles Metal Systems ICC No. 1715 Products for Power Driven Fastners for Plate Nailing

Manfacture	Product	ICC No.
Ramset/Red Head	1500, 1600 \$ 1900	1639
Simpson Strong Tie	PHN22 Steel Plate PHN72 Wood Plate	4546
Remington	SP125, SP300 SP SP300, SPW300 MP	5067
Hilti	0.145 dia w/ I" Embed.	2388

All pins shall have a diameter of 0.145", and be of sufficient length to provide I" embedment into concrete, shall be placed with 6" from plate ends and shall have 3/4" diameter steel washers.



Mood Stud Wall

understanding

Project Owner and Address:

equirements and is provided to assist in u

Searing Partitions and Mood Stud

Interio

9

Detail Non-B

SHEET OF